



Energy Kernel Battery Power Co., Ltd.

Product Specification

Features:

- Our BB-390B/U battery designs according to Military Standards.
- This is high performance rechargeable Nickel Metal Hydride battery
- High capacity, performance verified, hermetically sealed, NI-MH cells.
- Protection against short circuit and improper charge.
- High reliability due to all welded Construction.
- Unit contains safety vented cells
- 100% final testing



Items	Specification
Model no	PTO-390/LCD 117.6Wh
Average Voltage	Typical: 12.0V or 24.0V Final: 10.0V or 20.0V
Nominal Capacity	9.8Ah in 12V Mode 4.9Ah in 24V Mode
Pulse Capability(5 seconds)	Up to 18A continuous
Dimensions	112*127*61mm
Weight	1.8kg
Operating Temp	-20°C to +40°C
Storage Temp	-20°C to +55°C
Exterior/Housing	Hard Plastic Case
Terminals/Connect	6 pin polarized socket SC-C-179495
Absolute State of Charge Display	2 Separate 5 Segment LCDs with Constant Display
Replacement for	BB-590/U, BB-2590/U, BB-390/U, BB-490/U, BA-5590/U, BA-5390/U, BA-5290/U, BA-3590/U, and variants
APPLICATIONS	PRC-104, PRC-119, PRC-117, FALCON(AN/PRC-138/117, KY-57) MXF430(V), AN/PSC-5, M22, JAVELIN, LRAS